

Safety Data Sheet LUSTRE 3600

SECTION 1- PRODUCT IDENTIFICATION

PRODUCT NAME : LUSTRE 3600
SYNONYMS : Product is a mixture: No synonyms are available
PRODUCT USE : Highly Alkaline Material
SUPPLIER : WESMAR CO. INC.
SUPPLIER'S ADDRESS : 5720 204TH ST. SW, LYNNWOOD, WA 98036
 (206) 783-5344
EMERGENCY RESPONSE PHONE : PERS: 1-800-633-8253



SECTION 2 – HAZARD IDENTIFICATION

GHS – US CLASSIFICATION : H290 Metal corrosion Category 1
 H302 Harmful if swallowed
 : H314 Skin Corrosion Category 1A
 : H318 Serious Eye Damage Category 1

HAZARD PICTOGRAMS :



SIGNAL WORD :

DANGER

GHS LABEL ELEMENTS :

The product is classified and labeled according to the Globally Harmonized System (GHS).

GHS PHYSICAL HAZARDS :

H290 May be corrosive to metals.

GHS HEALTH HAZARDS :

H302 Harmful if swallowed
 H314 Causes severe skin burns and eye damage.
 H318 Causes serious eye damage.
 H370 Causes damage to respiratory system by inhalation.

GHS PRECAUTIONARY HAZARDS :

P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P103 Read label before use.
 P260 Do not breathe dust/fume/gas/mist/vapors/spray.
 P264 Wash skin and contaminated clothing thoroughly after handling.
 P270 Do not eat, drink or smoke when using this product.
 P280 Wear suitable protective gloves/protective clothing/eye protection/face protection.
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
 P303+P361 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P305+P351 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P305+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position.
 P310 Immediately call a POISON CENTER or doctor/physician.
 P330 Rinse mouth if ingested.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

CLASSIFICATION SYSTEM:

: NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme.

NFPA ratings (scale 0-4):

: Health = 3, Fire = 0, Reactivity = 1

Safety Data Sheet LUSTRE 3600

HMIS ratings (scale 0-5): : Health = 3, Fire = 0, Reactivity = 1

SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL CHARACTERIZATION : Mixtures
DESCRIPTION : Mixture of the substances listed below with nonhazardous additions.

COMPONENT	PERCENT	CAS #	EC #	GHS CLASS
Potassium Hydroxide	10-20	1310-58-3	215-181-3	Metal Corr Cat 1, Skin Corr Cat 1A Eye Dam Cat 1, Acute Tox Cat 4
Ethylenediamine Tetraacetate Na Salt	< 2	64-02-8	200-573-9	Skin Irrit Cat 2, Eye Dam Cat 2A
Tetrapotassium Pyrophosphate	< 2	7320-34-5	230-785-7	Not Established
Potassium Silicate	< 2	1312-76-1	215-199-1	Skin Irrit Cat 2, Eye Irrit Cat 2

Corr. = Corrosion, Dam. = Damage, Cat = Category, Tox = Toxicity, Irrit = Irritant.

Also contains non hazardous biodegradable surfactant(s).

SECTION 4 – FIRST AID MEASURES

EYE CONTACT : Immediately flush eyes with water for at least 15 minutes. Hold eyelids open to ensure adequate flushing. Get immediate medical attention.

SKIN CONTACT : Remove contaminated clothing and shoes. Wash affected skin area with soap and water. Delayed skin damage is possible if product is not completely washed off. Get immediate medical attention.

SWALLOWING (INGESTION) : If ingested, dilute swallowed material by drinking water. DO NOT INDUCE VOMITING. Never give anything by mouth to an unconscious person. Get immediate medical attention.

INHALATION : Remove to fresh air. Get immediate medical attention.

GENERAL MEASURES : Never give anything by mouth to an unconscious person. Rescue personnel must wear appropriate protective equipment during removal of victims from contaminated areas. Treat symptomatically and supportively.

SECTION 5 – FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA : Water spray, fog, carbon dioxide, foam, dry chemical

SPECIAL HAZARDS (FIRE) : Not flammable. Contains sodium hypochlorite which may act as an oxidizer in some cases intensifying a fire.

EXPLOSION HAZARDS : Product is not explosive.

REACTIVITY (FIRE) : Thermal decomposition generates: Corrosive vapors. If the product is involved in a fire, it can release explosive hydrogen gas. When heated to decomposition, emits toxic fumes. May be corrosive to metals.

SPECIAL INSTRUCTIONS TO FIRE FIGHTERS

PRECAUTIONARY MEASURES : Exercise caution when fighting any chemical fire.

FIREFIGHTING INSTRUCTIONS : Use water spray or fog for cooling exposed containers.

PROTECTION DURING FIREFIGHTING : Do not enter fire area without proper protective equipment, including respiratory protection.

HAZARDOUS COMBUSTION PRODUCTS : Potassium oxides. May liberate toxic gases. Sodium oxides. Phosphorous oxides. Nitrogen oxides. Carbon oxides (CO, CO₂). Explosive Hydrogen gas.

OTHER INFORMATION (FIRE) : Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Safety Data Sheet LUSTRE 3600

- PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES** : Restrict access to keep out unauthorized or unprotected personnel. Wear protective equipment. Avoid inhalation and direct contact.
- ENVIRONMENTAL PRECAUTIONS** : Keep spilled material away from sewage/drainage systems and waterways. This product contains a U.S. EPA Reportable Quantity (RQ) substance. If amounts exceeding the Reportable Quantity are released, notification of the National Response Center (800) 424-8802 is required. See section 15 for more information.
- METHODS AND MATERIALS FOR CONTAINMENT AND CLEAN UP** : All clean-up personnel must be properly trained. Confine the spill and remove incompatible materials and ignition sources. Ensure adequate ventilation. Secure the source of the leak if conditions are safe. Neutralize spill and collect using an appropriate absorbent material such as clay or vermiculite. Place waste in an appropriate container for disposal. Use care during clean-up to avoid exposure to the material and injury from broken containers.

SECTION 7 – HANDLING AND STORAGE

- PRECAUTIONS FOR SAFE HANDLING** : Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and again when leaving work. Do not eat, drink or smoke when using this product. Wash hands and forearms thoroughly after handling.
- CONDITIONS FOR SAFE STORAGE** : Store in a dry, cool and well ventilated place. Keep container closed when not in use. Keep/store away from extremely high or low temperatures, direct sunlight, heat and incompatible materials (Strong acid, Strong oxidizers).



SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

- TLV (THRESHOLD LIMIT VALUE)** : The TLV in section III is the ACGIH/TLV-TWA (threshold limit value/time weighted average concentration for an eight hour work day). The STEL is the short term exposure limit and the (Ceil) is the ceiling limit.

COMPONENT	OSHA PEL – TWA	ACGIH TLV-Ceiling	ACGIH – STEL
Potassium Hydroxide	2 mg/m ³ (Ceiling)	2mg/m ³	2mg/m ³ (Ceiling)
Ethylenediamine Tetraacetate Na Salt	Not Established	Not Established	Not Established
Tetrapotassium Pyrophosphate	Not Established	Not Established	Not Established
Potassium Silicate	Not Established	Not Established	Not Established

- EYE PROTECTION** : Wear chemical splash goggles or face shield.
- SKIN PROTECTION** : Minimize contact with product. Wear chemical resistant coveralls, boots, gloves, apron and/or suitable long-sleeved clothing.
- RESPIRATORY PROTECTION** : In case of brief exposure use respiratory filter device. In case of intensive or longer exposure, use respiratory protective device that is independent of circulating air.
- VENTILATION** : Ensure adequate ventilation.
- ADDITIONAL MEASURES** : Emergency eyewash and safety shower facilities should be available in the immediate work area.
- REQUIRED WORK/HYGIENE** : Wash hands thoroughly after handling. Keep away from all food stuffs, beverages and feed. Do not eat, drink or smoke in work area.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Safety Data Sheet LUSTRE 3600

APPEARANCE	: Clear red liquid with mild odor.
ODOR	: Mild odor
ODOR THRESHOLD	: Not available
PH	: > 12 AS IS
MELTING POINT/FREEZING POINT	: Not available
BOILING POINT	: Not available
FLASHPOINT	: Not applicable
EVAPORATION RATE	: Not available
FLAMMABILITY	: Non flammable, Non combustible
LOWER FLAMMABILITY LIMIT	: Not applicable
UPPER FLAMMABILITY LIMIT	: Not applicable
VAPOR PRESSURE	: Not available
VAPOR DENSITY (AIR=1)	: Not available
RELATIVE DENSITY	: 1.19
SOLUBILITY IN WATER	: Soluble in water
PARTITION COEFFICIENT n-OCTANOL/WATER	: Not available
AUTOIGNITION TEMPERATURE	: Not available
DECOMPOSITION TEMPERATURE	: Not available

SECTION 10 – STABILITY AND REACTIVITY

REACTIVITY	: Thermal decomposition generates: Corrosive vapors. If the product is involved in a fire, it can release explosion hydrogen gas. When heated to decomposition, emits toxic fumes. May be corrosive to metals.
STABILITY	: Stable under recommended storage conditions.
HAZARDOUS CONDITIONS TO AVOID	: Direct sunlight. Extremely high or low temperatures. Heat. Combustible materials. Incompatible materials.
INCOMPATIBLE MATERIALS	: Strong acids. Strong oxidizers. Soft metals. May be corrosive to metal.
HAZARDOUS DECOMPOSITION PRODUCTS	: Carbon oxides (CO, CO ₂). Thermal decomposition generates: Corrosive vapors. Toxic gases. Hydrogen gas. Nitrogen oxides. Phosphorous oxides. Sodium oxides. Potassium oxides.

SECTION 11 – TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION	: Potassium Hydroxide
ACUTE TOXICITY	: Draize test, rabbit, skin: 50 mg/24H Severe; Oral, rat: LD50 = 273 mg/kg; LD50 values: Potassium Hydroxide: Oral (rat): 214 mg/kg. LC50 dermal and inhalation: Not listed.
EYE CONTACT	: Causes severe eye damage.
SKIN CONTACT	: Causes skin burns. Onset of symptoms may be delayed following exposure.
INHALATION	: Corrosive to respiratory tract.
INGESTION	: May be harmful if swallowed. Ingestion may cause chemical burns, pain, vomiting, difficulty breathing and other gastrointestinal effects.
CARCINOGENICITY	: The components of this product are not classified as carcinogenic by OSHA, NTP IARC or CA Prop 65.
MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE	: Asthma and other respiratory conditions, skin disorders.
TOXICOLOGICAL INFORMATION	: Ethylenediamine Tetraacetate
ACUTE TOXICITY	: LD50 Oral (rat): 630 - 1,260 mg/kg,
INHALATION LC50	: No data available

Safety Data Sheet LUSTRE 3600

DERMAL LD50	:	No data available
OTHER INFORMATION ON ACUTE TOXICITY	:	No data available
ECOLOGICAL INFORMATION ECOTOXICITY	:	Tetrapotassium Pyrophosphate 48-hr EC50 Daphnia magna: > 100 mg/l, Practically Nontoxic 96-hr LC50 Mysid Shrimp > 100 mg/l, Practically Nontoxic 96-hr LC50 Rainbow trout: > 100 mg/l, Practically Nontoxic.
ENVIRONMENTAL FATE	:	Phosphates: Inorganic phosphates, including this product, at high concentrations in the environment have the potential to cause eutrophication in aquatic systems. This condition is characterized by excessive algal growth, and subsequent decreases in oxygen levels. In general, proper use and disposal of this product should pose no adverse ecological risk.
TOXICOLOGICAL INFORMATION ACUTE TOXICITY	:	Potassium Silicate The acute oral toxicity of this product has not been tested. When chemically similar sodium silicates were tested on a 100% solids basis, their single dose acute oral LD50 in rats ranged from 1500 mg/kg to 3200 mg/kg. The acute oral lethality resulted from nonspecific causes. This product contains approximately 39.2% potassium silicate.
ACUTE IRRITATION	:	This material has not been tested for primary eye irritation. However, on the basis of its similarity to sodium silicate solutions in composition and alkalinity it is regarded as an eye irritant. When tested for primary skin irritation potential, similar potassium silicate solution produced no irritation to intact skin, but well defined irritation to abraded skin. Human experience confirms that irritation occurs when potassium silicates get on clothes at the collar, cuffs or other areas where abrasion may occur.

SECTION 12 – ECOLOGICAL INFORMATION
--

ECOLOGICAL INFORMATION ECOTOXICITY	:	Potassium Hydroxide Fish: Mosquito Fish: LC50 = 80.0 mg/L; 24 Hr.; Unspecified No data available.
ENVIRONMENTAL PHYSICAL	:	No information found.
OTHER PERSISTENCE AND DEGRADABILITY	:	No relevant information available.
BIOACCUMULATIVE POTENTIAL NOTES	:	No relevant information available. Water hazard class 1 (Self assessment): slightly hazardous for water. Do not allow undiluted product or large quantities of this product to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or un-neutralized. Rinse off larger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms.
ECOLOGICAL INFORMATION ECOTOXICITY	:	Ethylenediamine Tetraacetate No data available.
PERSISTENCE AND DEGRADABILITY	:	No data available.
BIOACCUMULATIVE POTENTIAL	:	No data available.
ECOLOGICAL INFORMATION ECOTOXICITY	:	Tetrapotassium Pyrophosphate 48-hr EC50 Daphnia magna: > 100 mg/l, Practically Nontoxic

Safety Data Sheet

LUSTRE 3600

- 96-hr LC50 Mysid Shrimp > 100 mg/l, Practically Nontoxic
 96-hr LC50 Rainbow trout: > 100 mg/l, Practically Nontoxic.
- ENVIRONMENTAL FATE** : Phosphates: Inorganic phosphates, including this product, at high concentrations in the environment have the potential to cause eutrophication in aquatic systems. This condition is characterized by excessive algal growth, and subsequent decreases in oxygen levels. In general, proper use and disposal of this product should pose no adverse ecological risk.
- ECOLOGICAL INFORMATION** : **Potassium Silicate**
ECOTOXICITY : The ecotoxicity of potassium silicate has not been tested. The following data is reported for chemically similar sodium silicates on a 100% solids basis: A 96 hour median tolerance for fish (*Gambusia affinis*) of 2320 ppm; a 96 hour median tolerance for water fleas (*Daphnia magna*) of 247 ppm; a 96 hour median tolerance for snail eggs (*Lymnea*) of 632 ppm; and a 96 hour median tolerance for Amphipoda of 160 ppm. This product contains approximately 39.2% potassium silicate.
- ENVIRONMENTAL FATE** : This material is not persistent in aquatic systems, but its high pH when undiluted or un-neutralized is acutely harmful to aquatic life. Diluted material rapidly depolymerizes to yield dissolved silica in a form that is indistinguishable from natural dissolved silica. It does not contribute to BOD. This material does not bioaccumulate except in species that use silica as a structural material such as diatoms and siliceous sponges.

SECTION 13 – DISPOSAL CONSIDERATIONS

- WASTE DISPOSAL RECOMMENDATIONS** : This product must be disposed of in accordance with Federal, state and local environmental regulations. Discarded materials may be considered hazardous waste due to pH/corrosivity. It is the responsibility of the product user to determine at the time of disposal whether a material containing, or derived from this product, should be classified as a hazardous waste.
- ECOLOGY-WASTE MATERIALS** : This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

SECTION 14 – TRANSPORTATION INFORMATION

- DOT/IMDG/ IATA PROPER SHIPPING NAME** : UN-1814, POTASSIUM HYDROXIDE, SOLUTION 8 PG-II
- HAZARD CLASS AND LABEL** : 8 (Corrosive)
- UN NUMBER** : UN-1814
- PACKAGING GROUP** : PG-II
- EPA REPORTABLE QUANTITY (RQ)** : 1000 LBS. (454 KG) as Potassium Hydroxide 100%.
- MARINE POLLUTANT** : Marine Pollutant
- EMERGENCY RESPONSE GUIDE** : ERG-154



SECTION 15 – REGULATORY INFORMATION

U.S. FEDERAL REGULATORY INFORMATION:

- LISTED CARCINOGEN** : Not listed
- TSC STATUS** : The ingredients of this product are listed on TSCA (Toxic Substances Control Act) inventory (40CFR 710.)
- SARA SECTION 302** : None
- SARA SECTION 311/312** : Immediate (acute) health hazard.

Safety Data Sheet

LUSTRE 3600

HAZARD CLASS
SARA SECTION 313 : Not Listed
NFPA HEALTH : 3
NFPA FLAMMABILITY : 0
NFPA REACTIVITY : 1


EUROPEAN UNION REGULATORY INFORMATION:

EC CLASSIFICATION : C: Corrosive, Xn: Harmful.
DSD/DPD RISK (R) PHRASES : R34: Causes severe burns.
R22: Harmful if swallowed.
DSD/DPD SAFETY (S) PHRASES : S1/2: Keep locked up and out of reach of children.
S18: Handle and open containers with care.
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S36/S37/39: Wear suitable protective clothing, gloves and eye/face protection.
S45: In case of accidents or if you feel unwell, seek medical advice immediately. Show label where possible.
S61: Avoid release to the environment.
S64: If swallowed, rinse mouth with water if victim is conscious.
DSD/DPD HAZARD SYMBOL : C: Corrosive, Xn: Harmful



CANADIAN REGULATORY INFORMATION

WHMIS CATEGORY : Class E: Corrosive: Potassium Hydroxide
Class D2B: Materials causing other toxic effects (TOXIC): Tetrapotassium Pyrophosphate
D1B: Poisonous and infectious material: Immediate and serious effects (TOXIC). Potassium Hydroxide



DOMESTIC SUBSTANCES LIST (DSL) : Listed
INGREDIENT DISCLOSURE LIST : Listed, This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the sds contains all of the information required by the CPR.

SECTION 16 – OTHER INFORMATION

DISCLAIMER : The information contained herein has been compiled from sources believed to be reliable and accurate to the best of our knowledge at this date. It is provided without warranty, expressed or implied, as to the results of use of this information or to the product to which it relates. Wesmar Co. assumes no responsibility for injury to any person or property resulting from any use of the material. Each user assumes the risk in their use of this product and should review the data and recommendations in the specific context of their intended use.

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act.
EINECS : European Inventory of Existing Commercial Chemical Substances
IMDG : International Maritime Code for Dangerous Goods
IARC : International Agency for Research on Cancer
IATA : International Air Transportation Association

Safety Data Sheet

LUSTRE 3600

ACGIH	: American Conference of Governmental Industrial Hygienists
NFPA	: National Fire Protection Association (USA)
NTP	: National Toxicology Program
SARA	: Superfund Amendments and Reauthorization Act
TSCA	: Toxic Substances Control Act
HMIS	: Hazardous Materials Identification System (USA)
WHMIS	: Workplace Hazardous Materials Information System
LC50	: Lethal concentration, 50 percent
LD50	: Lethal dose, 50 percent
STOT	: Systemic Target Organ Toxicity
DATE PREPARED	: JAN 12, 2011
DATE REVISED	: JAN 12, 2014