

Safety Data Sheet  
HOT DAWG

WM 5181, WM 5182  
WM 5183, WM 5185

SECTION 1 – PRODUCT IDENTIFICATION

PRODUCT NAME : HOT DAWG  
SYNONYMS : Product is a mixture: No synonyms are available  
PRODUCT USE : Alkaline Material  
SUPPLIER : WESMAR CO. INC.  
SUPPLIER'S ADDRESS : 5720 204<sup>TH</sup> ST SW, Lynnwood, WA 98036  
(206) 783-5344  
EMERGENCY RESPONSE PHONE : PERS: 1-800-633-8253



SECTION 2 – HAZARD IDENTIFICATION

GHS – US CLASSIFICATION : H290 Metal corrosion Category 1  
: H314 Skin Corrosion Category 1B  
: H318 Serious Eye Damage Category 1B  
: H412 Aquatic Acute Category 3

HAZARD PICTOGRAMS :



SIGNAL WORD :

**DANGER**

GHS LABEL ELEMENTS :

The product is classified and labeled according to the Globally Harmonized System (GHS).

GHS PHYSICAL HAZARDS :

H290 : May be corrosive to metals.  
H314 : Causes severe skin burns and eye damage.  
H318 : Causes serious eye damage.  
H412 : Harmful to aquatic life with long lasting effects.

GHS PRECAUTIONARY HAZARDS :

P101 : If medical advice is needed, have product container or label at hand.  
P102 : Keep out of reach of children.  
P103 : Read label before use.  
P260 : Do not breathe dust/fume/gas/mist/vapors/spray.  
P264 : Wash skin and contaminated clothing thoroughly after handling.  
P270 : Do not eat, drink or smoke when using this product.  
P280 : Wear suitable protective gloves/protective clothing/eye protection/face protection.  
P301+P330 : IF SWALLOWED. Rinse mouth. Do NOT induce vomiting.  
+P331  
P303+P361 : IF ON SKIN (or hair): Remove/Take off immediately all contaminated  
+P353 : clothing. Rinse skin with water/shower.  
: P305+P351 : IF IN EYES: Rinse cautiously with water for several minutes. Remove  
+P338 : contact lenses, if present and easy to do. Continue rinsing.  
: P305+P340 : IF INHALED: Remove victim to fresh air and keep at rest in a position.  
: P310 : Immediately call a POISON CENTER or doctor/physician.  
: P330 : Rinse mouth if ingested.  
: P405 : Store locked up.  
: P501 : Dispose of contents/container in accordance with  
local/regional/national/international regulations.

OSHA HAZARDS :

TARGET ORGANS :

CLASSIFICATION SYSTEM:

NFPA ratings (scale 0-4):

HMIS ratings (scale 0-5):

Target Organ Effect (Glycol Ether DPM)  
Kidney, Liver, Nerves (Glycol Ether DPM).  
NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme.  
Health = 2, Fire = 0, Reactivity = 0  
Health = 2, Fire = 0, Reactivity = 0

# Safety Data Sheet

## HOT DAWG

### SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

**CHEMICAL CHARACTERIZATION** : Mixtures  
**DESCRIPTION** : Mixture of the substances listed below with nonhazardous additions.

COMPONENT	PERCENT	CAS #	EC #	GHS CLASS
Potassium Hydroxide	5-10	1310-58-3	215-181-3	Metal Corr. Cat 1, Skin Corr Cat 1B Eye Dam Cat 1, Acute Tox (Oral) Cat 4
Dipropylene glycol methyl ether	5-10	34590-94-8	252-104-2	Eye Irrit: Cat 2B
Sodium Silicate	1-5	1344-09-8	215-687-4	Skin Irrit Cat 2, Eye Dam Cat 1
Propylene Glycol Butyl Ether	5-10	5131-66-8 & 18821-83-7	225-878-4	Skin Irrit. Cat 2, Eye Irrit. Cat 2A
Sodium Xylene Sulfonate	1-5	1300-72-7	215-090-9	Skin Irrit Cat 2, Eye Irrit Cat 2A
Alcohols, C9-11, Ethoxylated	1-5	68439-46-3	Not Found	Eye Irrit Cat 1, Skin Irrit Cat 2 Acute Tox Aquatic Cat 2, Toxic to Aquatic life w/ Long Lasting Effects Cat 3
b-Alanine, N-(2-carboxyethyl)-N-[3-(decyloxy)propyl]-, monosodium salt	1-5	64972-19-6	265-295-2	Not Found

Corr. = Corrosion, Dam. = Damage, Tox = Toxic, Irrit = Irritation, Cat = Category, Tox = Toxic, STOT-SE = Specific Target Organ Toxicity – Single Exposure.

### SECTION 4 – FIRST AID MEASURES

- EYE CONTACT** : Immediately flush eyes with water for at least 15 minutes. Hold eyelids open to ensure adequate flushing. Remove contact lenses, if present and easy to do so. Continue rinsing. Immediate call a POISON CENTER or doctor/physician.
- SKIN CONTACT** : Remove contaminated clothing and shoes. Wash affected skin area with water for at least 15 minutes. Delayed skin damage is possible if product is not completely washed off. Get immediate medical attention. Wash contaminated clothing before reuse.
- SWALLOWING (INGESTION)** : If ingested, dilute swallowed material by drinking water. DO NOT INDUCE VOMITING. Never give anything by mouth to an unconscious person. Immediate call a POISON CENTER or doctor/physician.
- INHALATION** : When symptoms occur, go into open air and ventilate suspected area. Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER/doctor/physician.
- GENERAL MEASURES** : Never give anything by mouth to an unconscious person. Rescue personnel must wear appropriate protective equipment during removal of victims from contaminated areas. Treat symptomatically and supportively.

### SECTION 5 – FIRE FIGHTING MEASURES

- EXTINGUISHING MEDIA** : Dry chemical, foam, water or carbon dioxide
- SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIREFIGHTER** : In the event of a fire, wear a NIOSH (USA) or CEN (EU) approved, positive pressure, self-contained breathing apparatus (SCUBA) and full protective clothing. Evacuate all non-essential personnel from the danger area.
- UNUSUAL FIRE AND EXPLOSION HAZARDS** : No further relevant information is available.

### SECTION 6 – ACCIDENTAL RELEASE MEASURES

## Safety Data Sheet HOT DAWG

- PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES** : Restrict access to keep out unauthorized or unprotected personnel. Wear protective equipment. Avoid inhalation and direct contact.
- ENVIRONMENTAL PRECAUTIONS** : Keep spilled material away from sewage/drainage systems and waterways. This product contains a U.S. EPA Reportable Quantity (RQ) substance. If amounts exceeding the Reportable Quantity are released, notification of the National Response Center (800) 424-8802 is required. See section 15 for more information.
- METHODS AND MATERIALS FOR CONTAINMENT AND CLEAN-UP** : All clean-up personnel must be properly trained. Confine the spill and remove incompatible materials and ignition sources. Ensure adequate ventilation. Secure the source of the leak if conditions are safe. Neutralize spill and collect using an appropriate absorbent material such as clay or vermiculite. Place waste in an appropriate container for disposal. Use care during clean-up to avoid exposure to the material and injury from broken containers.

### SECTION 7 – HANDLING AND STORAGE

- PRECAUTIONS FOR SAFE HANDLING** : Use with adequate ventilation. Wear proper protective equipment. Do not mix with water or acids without proper dilution and agitation to prevent a potentially violent reaction.
- CONDITIONS FOR SAFE STORAGE** : Store in closed, properly labeled containers. Protect containers from heat, physical damage, ignition sources and incompatible materials. Have emergency equipment for fires and spills readily available.



### SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

- TLV (THRESHOLD LIMIT VALUE)** : The TLV in section III is the ACGIH/TLV-TWA (threshold limit value/time weighted average concentration for an eight hour work day). The STEL is the short term exposure limit and the (Ceil) is the ceiling limit.

COMPONENT	OSHA PEL – TWA	ACGIH TLV – Ceiling	ACGIH – STEL
Potassium Hydroxide	2 mg/m <sup>3</sup> (Ceiling)	2 mg/m <sup>3</sup>	2 gm/m <sup>3</sup> (Ceiling)
Dipropylene Glycol Methyl Ether	100 ppm, 600 mg/m <sup>3</sup>	100 ppm	150 ppm
Sodium Silicate	Not Established	Not Established	Not Established
Propylene Glycol Butyl Ether (PnB)	Not Established	Not Established	Not Established
Sodium Xylene Sulfonate	Not Established	Not Established	Not Established
Alcohols, C9-11 Ethoxylated (91-6)	Not Established	Not Established	Not Established
b-Alanine, N-(2-carboxyethyl)-N-[3-(decyloxy)propyl]-, monosodium salt	Not Established	Not Established	Not Established

- EYE PROTECTION** : Wear chemical splash goggles or face shield.
- SKIN PROTECTION** : Minimize contact with product. Wear chemical resistant coveralls, boots, gloves, apron and/or suitable long-sleeved clothing.
- RESPIRATORY PROTECTION** : In case of brief exposure use respiratory filter device. In case of intensive or longer exposure, use respiratory protective device that is independent of circulating air.
- VENTILATION** : Ensure adequate ventilation.
- ADDITIONAL MEASURES** : Emergency eyewash and safety shower facilities should be available in the immediate work area.
- REQUIRED WORK/HYGIENE** : Wash hands thoroughly after handling. Keep away from all food stuffs, beverages and feed. Do not eat, drink or smoke in work area.



# Safety Data Sheet

## HOT DAWG

### SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	: Clear reddish liquid with mild odor
ODOR	: Mild odor
ODOR THRESHOLD	: Not available
PH	: > 12.5
MELTING POINT/FREEZING POINT	: Not available
BOILING POINT	: Not available
FLASHPOINT	: Non flammable, non combustible
EVAPORATION RATE	: Not available
FLAMMABILITY	: Not applicable
LOWER FLAMMABILITY LIMIT	: Not applicable
UPPER FLAMMABILITY LIMIT	: Not applicable
VAPOR PRESSURE	: Not available
VAPOR DENSITY (AIR=1)	: Not available
RELATIVE DENSITY	: 1.06
SOLUBILITY IN WATER	: Soluble in water
PARTITION COEFFICIENT n-OCTANOL/WATER	: Not available
AUTOIGNITION TEMPERATURE	: Not available
DECOMPOSITION TEMPERATURE	: Not available

### SECTION 10 – STABILITY AND REACTIVITY

STABILITY	: Stable under recommended storage conditions.
HAZARDOUS CONDITIONS TO AVOID	: No decomposition if used according to specifications.
INCOMPATIBLE MATERIALS	: Keep away from strong acids.
HAZARDOUS DECOMPOSITION PRODUCTS	: No dangerous decomposition products known.

### SECTION 11 – TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION	: <b>Potassium Hydroxide</b>
ACUTE TOXICITY	: LD50 Oral (rat): 214 mg/kg, LD50 Dermal: Not Determined. LC50 Inhalation: Not determined. When in solution, this material will affect all tissues with which it comes in contact. The severity of the tissue damage is a function of its concentration, the length of tissue contact time, and local tissue conditions. After exposure there may be a time delay before irritation and other effects occur. This material is a strong irritant and is corrosive to the skin, eyes, and mucous membranes. This material may cause severe burns and permanent damage to any tissue with which it comes into contact.
CARCINOGENICITY	: This product is not classified as a carcinogen by NTP, IARC or OSHA.
TOXICOLOGICAL INFORMATION	: <b>Dipropylene Glycol Methyl Ether</b>
ACUTE TOXICITY	: LD50 values: Oral LD50: 5152 mg/kg (rat). LC50 dermal and inhalation: Not listed. Eyes: Rabbit: Mild Irritation: 25 hours.
CARCINOGENICITY	: No component of this product present at levels greater than or equal to 0.1% is identified as probable or confirmed human carcinogen by IARC, ACGIH, NTP, and OSHA.

## Safety Data Sheet

### HOT DAWG

<b>TOXICOLOGICAL INFORMATION</b>	: <b>Sodium Silicate</b>
<b>ACUTE TOXICITY</b>	: LD50 Oral (Rat): 1153 mg/kg, LD50 Dermal (Rabbit): 4640 mg/kg. Sodium silicate is a type of amorphous silica and does not cause pulmonary silicosis.
<b>CARCINOGENICITY</b>	: This product is not classified as a carcinogen by NTP, IARC or OSHA.
<b>TOXICOLOGICAL INFORMATION</b>	: <b>Propylene Glycol Butyl Ether</b>
<b>ACUTE TOXICITY</b>	: LD 50 Rat: 2,200 mg/kg
<b>ACUTE INHALATION TOXICITY</b>	: No data available
<b>ACUTE DERMAL TOXICITY</b>	: LD 50 Rabbit: 3,100 mg/kg
<b>TOXICOLOGICAL INFORMATION</b>	: <b>Sodium Xylene Sulfonate</b>
<b>ROUTES OF ENTRY</b>	: Absorbed through skin and/or eye contact.
<b>ACUTE TOXICITY</b>	: LD50 Oral (rat): 2500 mg/kg,
<b>CHRONIC EFFECTS ON HUMANS</b>	: Contains material which may cause damage to the following organs: liver
<b>SPECIAL REMARKS ON TOXICITY TO ANIMALS</b>	: TDL (rat): Route: skin; Dose: 3380 mg/kg/17D intermittent; Toxic effects: changes in liver weight TDL (rat): Route: skin; Dose: 35 gm/kg/14W intermittent; Toxic effects: dermatitis, other (skin and appendages). (Sodium Xylene Sulfonate).
<b>TOXICOLOGICAL INFORMATION</b>	: <b>Alcohols, C9-11, Ethoxylated</b>
<b>ACUTE TOXICITY</b>	: LD50 Oral (rat): 1,378 mg/kg,
<b>INHALATION LC50</b>	: No data available.
<b>DERMAL LD50</b>	: LD50 Dermal (rat): > 5,000 mg/kg.
<b>PRIMARY SKIN IRRITATION</b>	: (Rabbit) Moderate to severely irritating.
<b>PRIMARY EYE IRRITATION</b>	: (Rabbit) Severely irritating.
<b>TOXICOLOGICAL INFORMATION</b>	: <b>b-Alanine, N-(2-carboxyethyl)-N-[3-(decyloxy)propyl]-, monosodium salt</b>
<b>ACUTE TOXICITY</b>	: LD50 Oral (rat): 16,800 mg/kg, LD50 Dermal and LC50 Inhalation: Not available.
<b>CHRONIC EFFECTS ON HUMANS</b>	: Not available
<b>IRRITATION AND CORROSION</b>	: Skin and Eye irritant.

#### SECTION 12 – ECOLOGICAL INFORMATION

<b>ECOLOGICAL INFORMATION</b>	: <b>Potassium Hydroxide</b>
<b>AQUATIC TOXICITY</b>	: This material is alkaline and may raise the pH of surface waters with low buffering capacity. This material has exhibited moderate toxicity to aquatic organisms.
<b>FRESHWATER FISH TOXICITY</b>	: LC50 (Mosquito fish): 80 mg/L/96 hr (static bioassay in fresh water at 18-19 C) LC50 (Fathead Minnow): 179 mg/L/96 hr (static at 22.3-24.7 C)
<b>INVERTEBRATE TOXICITY</b>	: EC50 (Daphnia magna): 60 mg/L/48 hr (static bioassay at 20.3-20.7 C)
<b>FATE &amp; TRANSPORT</b>	: This material will disassociate into ionic form in the aquatic environment. Natural carbon dioxide will slowly neutralize this material.
<b>BIODEGRADATION</b>	: This material does not bio-concentrate.
<b>BIOCONCENTRATION</b>	: This material has exhibited slight toxicity to terrestrial organisms.
<b>ADDITIONAL ECOLOGICAL INFORMATION</b>	
<b>ECOLOGICAL INFORMATION</b>	: <b>Dipropylene Glycol Methyl Ether</b>
<b>ECOTOXICITY (aquatic and terrestrial, where available):</b>	
<b>ACUTE FISH TOXICITY</b>	: LC50 / 96 hours Fathead Minnow - >10,000 mg/L
<b>TOXICITY TO DAPHNIA</b>	: EC50 / 48 hours Water flea - 1,919 mg/L
<b>PERSISTENCE AND DEGRADABILITY</b>	: No data available.
<b>BIOACCUMULATIVE POTENTIAL</b>	: No data available.
<b>ECOLOGICAL INFORMATION</b>	: <b>Sodium Silicate</b>
<b>ECOTOXICITY AQUATIC</b>	: This material has exhibited moderate toxicity to aquatic organisms.
<b>FATE AND TRANSPORT</b>	: This material is inorganic and not subject to biodegradation.

# Safety Data Sheet

## HOT DAWG

<b>BIODEGRADATION PERSISTENCE</b>	:	This material is believed to persist in the environment.
<b>BIOCONCENTRATION</b>	:	This material is not expected to bio-concentrate in organisms.
<b>ADDITIONAL ECOLOGICAL INFORMATION</b>	:	This material has exhibited slight to toxicity to terrestrial organisms.
<b>ECOLOGICAL INFORMATION</b>	:	<b>Propylene Glycol Butyl Ether</b>
<b>ECOTOXICITY: TOXICITY TO FISH</b>	:	No data available
<b>TOXICITY TO DAPHNIA</b>	:	No data available
<b>TOXICITY TO ALGAE</b>	:	No data available
<b>TOXICITY TO BACTERIA</b>	:	No data available
<b>ECOLOGICAL INFORMATION</b>	:	<b>Sodium Xylene Sulfonate</b>
<b>ECOTOXICITY</b>	:	Not available
<b>BOD5 AND COD</b>	:	Not available
<b>PRODUCTS OF BIODEGRADATION</b>	:	Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.
<b>TOXICITY OF THE PRODUCTS OF BIODEGRADATION</b>	:	: The product itself and its products of degradation are not toxic.
<b>ECOLOGICAL INFORMATION</b>	:	<b>Alcohols, C9-11, Ethoylated 91-6</b>
<b>ECOTOXICITY</b>	:	LC50 Rainbow Trout: 1-10 mg/l, 96hr. Value estimated from tests on similar products. LC50 Fathead Minnow: 6 mg/l, 96hr. Value estimated from tests on similar products.
<b>BIODEGRADABILITY PERSISTENCE AND DEGRADABILITY</b>	:	Readily biodegradable. No data available.
<b>BIOACCUMULATIVE POTENTIAL</b>	:	No data available.
<b>ECOLOGICAL INFORMATION</b>	:	<b>b-Alanine, N-(2-carboxyethyl)-N-[3-(decyloxy)propyl ],monosodium salt</b>
<b>AQUATIC TOXICITY</b>	:	LC50 (96 h) : 60.6 mg/l Species : Fathead minnow (Pimephales promelas). LC50 (24 h) : 100 - 250 mg/l Species : Fathead minnow (Pimephales promelas).
<b>TOXICITY: OTHER ORGANISMS</b>	:	No data available.
<b>BIODEGRADABILITY</b>	:	Inherently biodegradable, not readily biodegradable.
<b>MOBILITY</b>	:	No data available.
<b>BIOACCUMULATION</b>	:	No data available.

### SECTION 13 – DISPOSAL CONSIDERATIONS

<b>WASTE DISPOSAL</b>	:	This product must be disposed of in accordance with Federal, state and local environmental regulations. Discarded materials may be considered hazardous waste due to pH/corrosivity. It is the responsibility of the product user to determine at the time of disposal whether a material containing, or derived from this product, should be classified as a hazardous waste
-----------------------	---	---

### SECTION 14 – TRANSPORTATION INFORMATION

<b>DOT/IMDG/ IATA PROPER SHIPPING NAME</b>	:	UN-1814, POTASSIUM HYDROXIDE, SOLUTION 8, PG-II
<b>HAZARD CLASS AND LABEL</b>	:	8 (Corrosive)
<b>UN NUMBER</b>	:	UN-1814
<b>PACKAGING GROUP</b>	:	PG-II
<b>EPA REPORTABLE QUANTITY</b>	:	1000 LBS. (454 KG) as Potassium Hydroxide 100%.



# Safety Data Sheet

## HOT DAWG

(RQ)  
MARINE POLLUTANT : Not listed.  
EMERGENCY RESPONSE : ERG-154  
GUIDE

### SECTION 15 – REGULATORY INFORMATION

#### U.S. FEDERAL REGULATORY INFORMATION:

**LISTED CARCINOGEN** : Not listed  
**TSC STATUS** : The ingredients of this product are listed on TSCA (Toxic Substances Control Act) inventory (40CFR 710.)  
**SARA SECTION 302** : **EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355, APPENDIX A):**  
No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.  
**SARA SECTION 311 HAZARD CATEGORIES (40 CFR 370):** : Immediate (acute) health hazard. (Dipropylene glycol methyl ether).  
**SARA SECTION 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.  
**NFPA HEALTH** : 2  
**NFPA FLAMMABILITY** : 0  
**NFPA REACTIVITY** : 0

#### EUROPEAN UNION REGULATORY INFORMATION:

**EC CLASSIFICATION** : C: Corrosive, Xn: Harmful.  
**DSD/DPD RISK (R) PHRASES** : R34: Causes severe burns.  
R22: Harmful if swallowed.  
**DSD/DPD SAFETY (S) PHRASES** : S1/2: Keep locked up and out of reach of children.  
S18: Handle and open containers with care.  
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
S36/S37/39: Wear suitable protective clothing, gloves and eye/face protection.  
S45: In case of accidents or if you feel unwell, seek medical advice immediately. Show label where possible.  
S61: Avoid release to the environment.  
S64: If swallowed, rinse mouth with water if victim is conscious.



**DSD/DPD HAZARD SYMBOL** : C: Corrosive, Xn: Harmful

#### CANADIAN REGULATORY INFORMATION

**WHMIS CATEGORY** : Class E: Corrosive, Class D2B: Materials that cause other toxic effects (TOXIC).  
D1B: Poisonous and infectious material: Immediate and serious effects (TOXIC). Potassium Hydroxide  
**DOMESTIC SUBSTANCES LIST (DSL)** : Listed



**INGREDIENT DISCLOSURE LIST** : Listed, This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the sds contains all of the information required by the CPR.



# Safety Data Sheet

## HOT DAWG

### SECTION 16 – OTHER INFORMATION

<b>DISCLAIMER</b>	: The information contained herein has been compiled from sources believed to be reliable and accurate to the best of our knowledge at this date. It is provided without warranty, expressed or implied, as to the results of use of this information or to the product to which it relates. Wesmar Co. assumes no responsibility for injury to any person or property resulting from any use of the material. Each user assumes the risk in their use of this product and should review the data and recommendations in the specific context of their intended use.
<b>CERCLA</b>	: Comprehensive Environmental Response, Compensation, and Liability Act.
<b>EINECS</b>	: European Inventory of Existing Commercial Chemical Substances
<b>IMDG</b>	: International Maritime Code for Dangerous Goods
<b>IARC</b>	: International Agency for Research on Cancer
<b>IATA</b>	: International Air Transportation Association
<b>ACGIH</b>	: American Conference of Governmental Industrial Hygienists
<b>NFPA</b>	: National Fire Protection Association (USA)
<b>NTP</b>	: National Toxicology Program
<b>SARA</b>	: Superfund Amendments and Reauthorization Act
<b>TSCA</b>	: Toxic Substances Control Act
<b>HMIS</b>	: Hazardous Materials Identification System (USA)
<b>WHMIS</b>	: Workplace Hazardous Materials Information System
<b>LC50</b>	: Lethal concentration, 50 percent
<b>LD50</b>	: Lethal dose, 50 percent
<b>STOT</b>	: Systemic Target Organ Toxicity
<b>DATE PREPARED</b>	: JAN 12, 2015
<b>DATE REVISED</b>	: JAN 12, 2015