

SAFETY DATA SHEET

Revision Date 30-Apr-2015 Version 1

1. IDENTIFICATION

Product identifier

Product Name Wynn's Air Intake Cleaner

Other means of identification

Product Code WN A6601 Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use See directions provided with product

Uses advised against All other applications

Details of the supplier of the safety data sheet

Supplier Address Manufacturer Address Distributor

ITW Professional Automotive Products

3606 Craftsman Blvd. Lakeland, FL 33803

Company Phone Number 863-665-3338

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003583

E-mail address EHS@itwproap.com

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

| Acute toxicity - Inhalation (Gases) | Category 4 |
|--|------------|
| Acute toxicity - Inhalation (Dusts/Mists) | Category 4 |
| Skin corrosion/irritation | Category 2 |
| Serious eye damage/eye irritation | Category 2 |
| Specific target organ toxicity (single exposure) | Category 3 |
| Specific target organ toxicity (repeated exposure) | Category 2 |
| Aspiration toxicity | Category 1 |
| Flammable liquids | Category 1 |

Label elements

Emergency Overview

Danger

Harmful if inhaled

Causes skin irritation

Causes serious eye irritation

May cause drowsiness or dizziness

May cause damage to organs through prolonged or repeated exposure

May be fatal if swallowed and enters airways

Extremely flammable liquid and vapor



Appearance Clear Physical state Liquid Odor Solvent

Precautionary Statements - Prevention

Use only outdoors or in a well-ventilated area

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves/protective clothing/eye protection/face protection

Do not breathe dust/fume/gas/mist/vapors/spray

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

Precautionary Statements - Response

Get medical advice/attention if you feel unwell

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

If skin irritation occurs: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

May be harmful if swallowed. May be harmful in contact with skin. Toxic to aquatic life with long lasting effects. Harmful to aquatic life.

Unknown acute toxicity 1.61% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

substance(s)

| Chemical Name | CAS No | Weight-% | Trade Secret |
|---------------|-----------|----------|--------------|
| Xylene | 1330-20-7 | 10 - 30 | * |

| Solvent naphtha (petroleum), light aromatic | 64742-95-6 | 10 - 30 | * |
|---|------------|---------|---|
| Acetone | 67-64-1 | 7 - 13 | * |
| Ethylbenzene | 100-41-4 | 7 - 13 | * |
| 1,2,4-Trimethylbenzene | 95-63-6 | 7 - 13 | * |
| 1,3,5-Trimethylbenzene | 108-67-8 | 1 - 5 | * |
| Cumene | 98-82-8 | 1 - 5 | * |

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice Get medical advice/attention if you feel unwell.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Skin contact IF ON SKIN:. Wash skin with soap and water. If skin irritation persists, call a physician.

Wash contaminated clothing before reuse.

Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

Ingestion IF SWALLOWED:. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Call a physician.

Self-protection of the first aider

Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO2), Dry chemical, Foam

Unsuitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Flammable.

Explosion data

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Remove all sources of ignition. Use personal protective equipment as required.

Environmental precautions

Environmental precautions See Section 12 for additional ecological information. Do not flush into surface water or

sanitary sewer system.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Soak up with inert absorbent material.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid breathing

vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity).

Incompatible materials Strong oxidizing agents

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|------------------------------------|-------------------------------|---|---|
| Xylene 1330-20-7 | STEL: 150 ppm TWA: 100 ppm | TWA: 100 ppm TWA: 435 mg/m³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m³ | - |
| Acetone 67-64-1 | STEL: 750 ppm TWA: 500 ppm | TWA: 1000 ppm TWA: 2400 mg/m³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m³ (vacated) STEL: 2400 mg/m³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors (vacated) STEL: 1000 ppm | IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m³ |
| Ethylbenzene 100-41-4 | TWA: 20 ppm | TWA: 100 ppm TWA: 435 mg/m³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m³ | IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m³ STEL: 125 ppm STEL: 545 mg/m³ |
| 1,2,4-Trimethylbenzene 95-63-6 | - | - | TWA: 25 ppm TWA: 125 mg/m ³ |
| 1,3,5-Trimethylbenzene 108-67-8 | - | - | TWA: 25 ppm TWA: 125 mg/m ³ |

| Cumene 98-82-8 | TWA: 50 ppm | TWA: 50 ppm TWA: 245 mg/m³ (vacated) TWA: 50 ppm (vacated) TWA: 245 mg/m³ (vacated) S* | IDLH: 900 ppm TWA: 50 ppm TWA: 245 mg/m³ |
|-------------------|-------------|--|--|
|-------------------|-------------|--|--|

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear protective gloves and protective clothing.

appropriate.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of

equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical stateLiquidAppearanceClearOdorSolvent

Color amber

Odor threshold No information available

Property Values Remarks • Method

pH No information available
Melting point / freezing point
Boiling point / boiling range
Flash point
No information available
No information available
> 35 °C / 95 °F
3 °C / 37 °F

Evaporation rate No information available Flammability (solid, gas) No information available

Flammability Limit in Air

Upper flammability limit:No information availableLower flammability limit:No information availableVapor pressureNo information availableVapor densityNo information available

Relative density 0.87

Water solubility Insoluble in water

Solubility in other solvents
Partition coefficient
Autoignition temperature
Decomposition temperature
No information available
No information available
No information available

Kinematic viscosity 2 mm2/s

Dynamic viscosityNo information availableExplosive propertiesNo information availableOxidizing propertiesNo information available

Other Information

Softening point
Molecular weight
VOC Content (%)
Density
No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Excessive heat.

Incompatible materials

Strong oxidizing agents

Hazardous Decomposition Products

Carbon oxides

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation May cause irritation of respiratory tract.

Eye contact Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

Skin contact May cause skin irritation and/or dermatitis.

Ingestion Ingestion may cause irritation to mucous membranes.

| Chemical Name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|--|----------------------|--|---|
| Xylene 1330-20-7 | = 3500 mg/kg (Rat) | > 4350 mg/kg (Rabbit) > 1700 mg/kg (Rabbit) | = 29.08 mg/L (Rat) 4 h = 5000 ppm (Rat) 4 h |
| Solvent naphtha (petroleum), light aromatic 64742-95-6 | = 8400 mg/kg (Rat) | > 2000 mg/kg (Rabbit) | = 3400 ppm (Rat) 4 h |
| Acetone 67-64-1 | = 5800 mg/kg (Rat) | - | = 50100 mg/m³ (Rat) 8 h |
| Ethylbenzene 100-41-4 | = 3500 mg/kg (Rat) | = 15400 mg/kg (Rabbit) | = 17.2 mg/L (Rat) 4 h |
| 1,2,4-Trimethylbenzene 95-63-6 | = 3280 mg/kg (Rat) | > 3160 mg/kg (Rabbit) | = 18 g/m³ (Rat) 4 h |
| 1,3,5-Trimethylbenzene 108-67-8 | = 5000 mg/kg (Rat) | - | = 24 g/m³ (Rat) 4 h |
| Cumene 98-82-8 | = 1400 mg/kg (Rat) | = 12300 μL/kg(Rabbit) | > 3577 ppm (Rat) 6 h = 39000 mg/m³ (Rat) 4 h |

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

| | | | i digitally there in the direction of the | , |
|--------------------------|-------|----------|---|------|
| Chemical Name | ACGIH | IARC | NTP | OSHA |
| Xylene 1330-20-7 | - | Group 3 | - | - |
| Ethylbenzene 100-41-4 | A3 | Group 2B | - | Х |
| Cumene 98-82-8 | - | Group 2B | - | Х |

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer) Group 2B - Possibly Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humai Not classifiable as a human carcinogen

Group 1 - Carcinogenic to Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Chronic toxicity May cause adverse effects on the bone marrow and blood-forming system.

Target Organ Effects Central nervous system, Eyes, Respiratory system, Skin, Blood.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 4373 mg/kg
ATEmix (dermal) 2447 mg/kg
ATEmix (inhalation-gas) 6211 mg/l
ATEmix (inhalation-dust/mist) 3 mg/l
ATEmix (inhalation-vapor) 340473.1 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

14.71% of the mixture consists of components(s) of unknown hazards to the aquatic environment

| Chemical Name | Algae/aquatic plants | Fish | Crustacea |
|--|----------------------|---|---|
| Xylene 1330-20-7 | - | 13.4: 96 h Pimephales promelas mg/L LC50 flow-through 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through 19: 96 h Lepomis macrochirus mg/L LC50 7.711 - 9.591: 96 h Lepomis macrochirus mg/L LC50 static 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 780: 96 h Cyprinus carpio mg/L LC50 semi-static 780: 96 h Cyprinus carpio mg/L LC50 30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static | 3.82: 48 h water flea mg/L EC50 0.6: 48 h Gammarus lacustris mg/L LC50 |
| Solvent naphtha (petroleum), light aromatic 64742-95-6 | - | 9.22: 96 h Oncorhynchus mykiss mg/L LC50 | 6.14: 48 h Daphnia magna mg/L EC50 |
| Acetone 67-64-1 | - | 4.74 - 6.33: 96 h Oncorhynchus mykiss mL/L LC50 6210 - 8120: 96 h Pimephales promelas mg/L LC50 static 8300: 96 h Lepomis macrochirus mg/L LC50 | 10294 - 17704: 48 h Daphnia magna mg/L EC50 Static 12600 - 12700: 48 h Daphnia magna mg/L EC50 |

| | i e | | |
|------------------------|----------------------------------|--------------------------------------|------------------------------------|
| Ethylbenzene | 4.6: 72 h Pseudokirchneriella | | 1.8 - 2.4: 48 h Daphnia magna mg/L |
| 100-41-4 | subcapitata mg/L EC50 438: 96 h | mykiss mg/L LC50 static 9.6: 96 h | EC50 |
| | Pseudokirchneriella subcapitata | Poecilia reticulata mg/L LC50 static | |
| | mg/L EC50 2.6 - 11.3: 72 h | 4.2: 96 h Oncorhynchus mykiss | |
| | Pseudokirchneriella subcapitata | mg/L LC50 semi-static 7.55 - 11: 96 | |
| | mg/L EC50 static 1.7 - 7.6: 96 h | h Pimephales promelas mg/L LC50 | |
| | Pseudokirchneriella subcapitata | flow-through 32: 96 h Lepomis | |
| | mg/L EC50 static | macrochirus mg/L LC50 static 9.1 - | |
| | _ | 15.6: 96 h Pimephales promelas | |
| | | mg/L LC50 static | |
| 1,2,4-Trimethylbenzene | - | 7.19 - 8.28: 96 h Pimephales | 6.14: 48 h Daphnia magna mg/L |
| 95-63-6 | | promelas mg/L LC50 flow-through | EC50 |
| 1,3,5-Trimethylbenzene | - | 3.48: 96 h Pimephales promelas | 50: 24 h Daphnia magna mg/L |
| 108-67-8 | | mg/L LC50 | EC50 |
| Cumene | 2.6: 72 h Pseudokirchneriella | 6.04 - 6.61: 96 h Pimephales | 0.6: 48 h Daphnia magna mg/L |
| 98-82-8 | subcapitata mg/L EC50 | promelas mg/L LC50 flow-through | EC50 7.9 - 14.1: 48 h Daphnia |
| | | 4.8: 96 h Oncorhynchus mykiss | magna mg/L EC50 Static |
| | | mg/L LC50 flow-through 2.7: 96 h | |
| | | Oncorhynchus mykiss mg/L LC50 | |
| | | semi-static 5.1: 96 h Poecilia | |
| | | reticulata mg/L LC50 semi-static | |

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

| Chemical Name | Partition coefficient |
|-----------------------------------|-----------------------|
| Xylene 1330-20-7 | 2.77 - 3.15 |
| Acetone 67-64-1 | -0.24 |
| Ethylbenzene 100-41-4 | 3.118 |
| 1,2,4-Trimethylbenzene 95-63-6 | 3.63 |
| Cumene 98-82-8 | 3.55 |

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastesThis material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261).

Contaminated packaging Do not reuse container.

US EPA Waste Number U002 U239 D001

| Chemical Name | RCRA | RCRA - Basis for Listing | RCRA - D Series Wastes | RCRA - U Series Wastes |
|--------------------------|------|-----------------------------------|------------------------|------------------------|
| Xylene 1330-20-7 | - | Included in waste stream: F039 | - | U239 |
| Acetone 67-64-1 | - | Included in waste stream: F039 | - | U002 |
| Ethylbenzene 100-41-4 | - | Included in waste stream: F039 | - | - |
| Cumene 98-82-8 | - | - | - | U055 |

This product contains one or more substances that are listed with the State of California as a hazardous waste.

| Chemical Name | California Hazardous Waste Status |
|--------------------------|-----------------------------------|
| Xylene | Toxic |
| 1330-20-7 | Ignitable |
| Acetone 67-64-1 | Ignitable |
| Ethylbenzene 100-41-4 | Toxic Ignitable |
| Cumene 98-82-8 | Toxic Ignitable |

14. TRANSPORT INFORMATION

DOT

UN/ID no UN1993

Proper shipping name: Flammable liquids, n.o.s, (Contains, Acetone, Xylene,), Limited Quantity (LQ)

Hazard Class 3
Packing Group ||

IATA

UN/ID no UN1993

Proper shipping name: Flammable liquid, n.o.s, (Contains, Xylene,)

Hazard Class 3
Packing Group ||

IMDG

UN/ID no UN1993

Proper shipping name: Flammable liquids, n.o.s, (Contains, Xylene, Acetone,), Limited Quantity (LQ)

Hazard Class 3 Packing Group II

15. REGULATORY INFORMATION

International Inventories

TSCA Complies **DSL/NDSL** Complies **EINECS/ELINCS** Complies Complies **ENCS IECSC** Complies Complies **KECL PICCS** Complies Complies **AICS**

Leaend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

<u>SARA 313</u>

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

| Chemical Name | SARA 313 - Threshold Values % |
|----------------------------------|-------------------------------|
| Xylene - 1330-20-7 | 1.0 |
| 1,2,4-Trimethylbenzene - 95-63-6 | 1.0 |
| Ethylbenzene - 100-41-4 | 0.1 |
| Isopropanol - 67-63-0 | 1.0 |
| Cumene - 98-82-8 | 1.0 |

SARA 311/312 Hazard Categories

Acute health hazard No
Chronic Health Hazard No
Fire hazard Yes
Sudden release of pressure hazard No
Reactive Hazard No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

| Chemical Name | CWA - Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA - Hazardous Substances |
|--------------------------|--------------------------------|------------------------|---------------------------|-------------------------------|
| Xylene 1330-20-7 | 100 lb | - | - | Х |
| Ethylbenzene 100-41-4 | 1000 lb | X | Х | Х |

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

| Chemical Name | Hazardous Substances RQs | CERCLA/SARA RQ | Reportable Quantity (RQ) |
|---------------|--------------------------|----------------|--------------------------|
| Xylene | 100 lb | - | RQ 100 lb final RQ |
| 1330-20-7 | | | RQ 45.4 kg final RQ |
| Acetone | 5000 lb | - | RQ 5000 lb final RQ |
| 67-64-1 | | | RQ 2270 kg final RQ |
| Ethylbenzene | 1000 lb | - | RQ 1000 lb final RQ |
| 100-41-4 | | | RQ 454 kg final RQ |
| Cumene | 5000 lb | - | RQ 5000 lb final RQ |
| 98-82-8 | | | RQ 2270 kg final RQ |

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

| Chemical Name | California Proposition 65 | |
|-------------------------|---------------------------|--|
| Ethylbenzene - 100-41-4 | Carcinogen | |
| Cumene - 98-82-8 | Carcinogen | |

U.S. State Right-to-Know Regulations

| Chemical Name | New Jersey | Massachusetts | Pennsylvania |
|------------------------------------|------------|---------------|--------------|
| Xylene 1330-20-7 | X | X | X |
| Acetone 67-64-1 | X | X | X |
| 1,2,4-Trimethylbenzene 95-63-6 | X | X | X |
| Isopropanol 67-63-0 | X | X | X |
| 1,3,5-Trimethylbenzene 108-67-8 | - | X | - |
| Diethylbenzene 25340-17-4 | Х | - | - |
| Cumene 98-82-8 | Х | X | X |

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

NFPA Health hazards 2 Flammability 4 Instability 0

Health hazards 2 Flammability 4 Physical hazards 0 Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date 30-Apr-2015

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet